

FIRE RESISTANCE HOLLOW CORE FLOORS


Ir. Arnold Van Acker

Contents

1. Overview test results world wide
2. First conclusions
3. Recent tests with premature shear failure
4. Phenomenon
5. Research Fellingner TNO Netherlands
6. Research carried out in Belgium
7. Design philosophy
8. Open questions
9. Recommendations for tests

Overview fire test

- First tests in Belgium in 1971 on 265 mm slabs



- one single hollow core unit
- length 6.00 m

First test

- 6 smooth strands Φ 12.5
- Shear failure at 36 min

Second test




- 6 indented strands Φ 12.5
- Shear failure at 29 min.

Third test

- 6 strands Φ 12.5 with oval central wire
- Shear failure at 33 min.

Overview fire test

- Test in Belgium in 1972 on 265 mm slab in light weight concrete




1 bar $\Phi 10$ in 2 open sleeves



Failure: longitudinal splitting after 76 min. exposure

Overview fire test


- Tests in Belgium in 1980 on floor composed of 3 units of 600 mm width, with topping and end beam



HC 15/600: bending
> 1/30 after 76 min.


HC 20/600: bending
> 1/30 after 126 min.

Cover strands 30 mm




Overview fire test

- Tests in Belgium in 1990 on floor composed of 3 units, with topping, end beam and bars in sleeves



HC 15/600:
bending $> 1/30$
after 182 min.





HC 20/600:
bending $> 1/30$
after 194 min.


Cover strands
45 mm

Overview fire tests

- Tests in Finland in 1985 - Rf 60 min.



Cover strands: 30 mm
Moisture: 2.3 %



Test loading:




a : no loading

b/c : $F = 40$ kN in the
middle of the span

d : $F = 84$ kN in the
middle of the span

Overview fire tests




- Tests in Finland in 1984 on HC 265 mm



- a: loading 10.8 kN/m^2
axis distance 35 mm
Rf 60 min.
- b: loading 1.25 kN/m^2
axis distance 65 mm
Rf 130 min.



Overview test results

- Tests Underwriters USA





Concrete frame around test floor

Test results HC world wide





Temperature profiles



Temperature profiles

- Large dispersion temperature measurements

Registered strandtemperatures in HC 400 - axis distance strands 55 mm



Influencing parameters

- Slab thickness
- Cover on strands
- Connection reinforcement at support
- Topping
- Obstruction thermal dilatation
- Concrete strength
- Moisture content
- Type of aggregates

First conclusions


- Shear is governing for slabs without support connections
- Bending failure when adequate connections
- Difficult to reach R_f 120 at some laboratories
- Large dispersion temperature registrations in same slab

More recent fire tests


- **Premature shear failure : tests in France, Denmark and Holland**
 - ⇒ **Phenomenon**
 - ⇒ **Real behaviour during a fire**
 - ⇒ **Research on shear capacity HC under fire**
 - ⇒ **Recommendations for fire tests**

More recent tests

□ Tests CTiCM France




Shear failure HC slabs after
32 minutes fire exposure



More recent tests

☐ Tests Danish Institute of Fire Technology



Test results:

HC 185

22 min. shear failure

HC 220



26 min. shear failure

HC 270


21 min. shear failure

More recent tests

□ Tests Danish Institute of Fire Technology






Hollow core floor
with cast in-situ
cantilever Loading
 23 kN/m^2





Phenomenon

- Tensile stresses in webs due to gradient




Induced thermal stresses

Tensile stresses exceeding concrete strength after already 20 minutes




Test TNO Delft



Calculation Univ. Liège (B)

Research Fellingner


□ Tests Fellingner at TNO The Netherlands



Tested units:	A 200	VBI slipform	B55	calcareous
	X 200	Spanbeton extrusion	B65	calcareous
	XB 200	Spanbeton		
	VX 265	Spanbeton		
	HVP 260	BetonSon extrusion	B65	Siliceous
	K 400	Dycore extrusion	B65	Siliceous

Research Fellingner TNO

□ Analysis existing HC test reports



Influence axis distance and load factor on failure type


Test results TNO

Web	loading:	Rf :	Failure:
A200	22%	96 min.	Anchorage
X200	16%	125	Flexure
XB200	18%	125	Anchorage
XB200 Restrained	18%	159	Flexure
VX265	23%	35	Shear-tension
VX265	23%	25	Long. shear
HVP260	23%	55	Shear-tension
K400	23%	60	Shear-tension
K400 Restrained	23%	30	Shear-tension
K400 Filled Cores	23%	24	Shear-tension
Slab			
XB200 filled cores	23%	117	Flexure
K400	23%	33	Shear-tension
VX265	23%	33	Shear-tension
HVP260	23%	40	Anchorage
HVP260	23%	42	Shear-tension
HVP 260	23%	39	Shear-tension

Research shear resistance HC

□ Programme carried out in Belgium

Loading: 100 kN



Test results:

T1: 83' no failure

T2: 120' no failure

T3: 120' no failure

T4: 120' no failure

Failure loading
after tests:

T1 : 178/254 kN - bending

T2 : 292/324 kn - Bending



T3 : 267/254 kN - bending

T4 : 305 kN - bending


305 kN - shear

Design considerations

❑ Need for adequate connections



Interlocking effect enables to take up shear forces. This can be realised by:






- Ties in casted open cores
- Ties in longitudinal joints
- Peripheral ties
- Reinforced topping
- Rigidity of the surrounding

Open questions


- Influence load percentage
- Fire resistance HC with non rigid supports
- Strategy to be followed by IPHA
 - ⇒ Dissemination existing knowledge
 - ⇒ Harmonisation national test procedures
 - ⇒ New specific test prescription in EN 1168
(longitudinal bars or concrete frame)
 - ⇒ etc.

Practical instructions for tests

- ↓ Never perform tests on single slabs without connections
- ↓ The test unit should be composed of more than one slab
- ↓ The slabs should be connected to supporting beams
- ↓ Provide tie-bars in the longitudinal joints or in open casted cores
- ↓ Keep the moisture content of the unit below 2.5% by drying
- ↓ Simulate the restraining effect of the surrounding structure, e.g. by longitudinal bars along the edges of the test unit
- ↓ The topping should contain only longitudinal bars, since transverse bars will cause horizontal splitting of the slab.
- ↓ The test load should not be larger than 50% of the variable load at room temperature.



Hollow core floors: safe in fire



**Thank you for
your kind attention**